

Standard: DIN 7444

Version: Drop forged, with short, strong profile shaft and reinforced striking end.

61 9000 – Extremely thin ring, exact tolerance jaw widths for working on bolts in very restricted places.

The ring is higher than standard nuts, thus jamming is impossible.

Stronger than any bolt.


Material:

61 9000 – Chrome alloy steel, painted green.

61 9160 – Chrome vanadium steel, phosphated.



61 9000


 61 9160 **HOLEX®**


Size = Width across flats mm	63A 61 9000 	66A 61 9160 HOLEX®	LxD×h 61 9000 mm	LxD×h 61 9160 mm
	Slogging ring spanner, straight			
24	—	XXX	—	165×44×15
27	—	XXX	—	180×45×15
30	—	XXX	—	190×51×16
32	XXX	XXX	195×47×24	190×54×16
34	—	XXX	—	190×56×18
36	XXX	XXX	195×52.4×26	210×58×18
41	XXX	XXX	200×59×29	225×64×19
46	XXX	XXX	250×65×32	240×73×20
50	XXX	XXX	280×70×35	250×84×24
55	XXX	XXX	300×76×38	260×84×24
60	XXX	XXX	300×82.5×42	280×90×25
65	XXX	XXX	325×90.5×45	300×99×26
70	XXX	XXX	355×97×48	330×114×32
75	XXX	XXX	360×103.5×51	330×114×32
80	XXX	XXX	440×110×57	360×125×37
85	XXX	XXX	440×117×57	360×125×37